



Reifengröße 12"	Load Index	Aussen-durch-messer mm	Reifen-breite mm	Tragkraft kg	Raddimen-sion	Anschluss	Mitten-loch in mm	ET	Gewicht kg	Bestell-nummer
145R12-C	86N	543	147	390/140km/h	4,5Jx12	100x4	57	0	14,7	401802.001
145R12-C	86N	530	147	530/140km/h	4,5Jx12	112x5	67	0	14,3	404353.001
145R12-C	86N	530	147	530/140km/h	4,5Jx12	112x5	67	30	14,6	404355.001
145R12-C	86N	543	147	450/140km/h	4Jx12	100x4	57	26	12,6	405171.001
155R12-C	88Q	556	156	450/140km/h	4Jx12	100x4	57	0	14,3	401803.002
155R12-C	88Q	550	157	560/140km/h	4Jx12	112x5	67	0	14,3	404356.002
155R12-C	88Q	550	157	560/140km/h	4,5Jx12	112x5	67	30	14,3	404358.002
155/70R12-C*	104/102N	523	157	900/140km/h	4,5Jx12	112x5	67	0	14,4	400214.002
155/70R12-C*	104/102N	523	157	900/140km/h	4,5Jx12	112x5	67	20	14,5	400216.002
155/70R12-C*	104/102N	523	157	900/140km/h	4,5Jx12	112x5	67	30	14,6	400168.002
185/60R12-C*	104N	527	185	900/140km/h	5,5Jx12	112x5	67	30	17,0	411565.002
195/60R12-C*	108/106N	535	200	900/140km/h	5,5Jx12	112x5	67	30	18,0	419470.001
225/55B12-C Kenda	112N	554	228	900/140km/h	7,00lx12	112x5	67	-4	17,2	407223.001
225/55B12-C Kenda	112N	554	228	900/140km/h	7,00lx12	112x5	67	10	17,2	401578.002
225/55R12-C*Maxxis	104N	554	228	900/140km/h	7,00lx12	112x5	67	10	17,2	401578.001

Hinweis: Nach 20km und höchstens 100km müssen die Radmuttern nachgezogen werden!

* = mit M+S Kennung

Andere Ausführungen auf Anfrage. Änderungen vorbehalten.