



Reifengröße 8"	Fabrikat	Aussen- durchmesser mm	Reifen- breite mm	Tragkraft	Reifendruck max. in bar	Index	Gewicht kg	Bestell- nummer
16,5x6,5-8	Trailermaxx	415	170	410/130km/h	5,00	77M	4,5	404392.001
16,5x6,5-8	Deli	415	170	365/130km/h	4,90	73M	4,5	404392.002
18,5x8,5-8	Deli	478	212	425/130km/h	3,50	78M	5,9	404393.002
4.00-8 6PR	Kenda	410	107	335/130km/h	6,20	71M	2,8	404394.003
4,00x8 Schlauch							0,23	409730.001
5.00x8 6PR	Deli	470	140	335/130km/h	5,20	77M	4,3	404395.003
5.00-8 Schlauch							0,48	414128.001
Reifengröße 10"	Fabrikat	Aussen- durchmesser mm	Reifen- breite mm	Tragkraft kg	Reifendruck max. in bar	Index	Gewicht kg	Bestell- nummer
20.5x8.00-10 (205/65-10)	Kenda	516	198	750/130km/h	6,25	98M	8,3	400157.003
20.5x10,0-10 (255/50-10)	Kenda	524	253	750/130km/h	6,25	98M	8,3	407411.002
145R10*	Trailermaxx	486	145	375/140km/h	3,00	74N	5,4	401974.001
145R10	Security	486	145	375/140km/h	3,00	74N	5,4	401974.002
145R10	Security	486	145	375/140km/h	3,50	84N	5,5	401974.003
4,50-10	Veloce	498	130	400/130km/h	4,30	76N	5,4	407926.003
5,00-10	Kenda	525	141	430/130km/h	3,50	79N	5,3	404396.002
5,00-10	Sava	525	141	430/140km/h	3,50	79N	5,3	404396.001
195/50B-10 (18x8,0-10)	Trailermaxx	460	187	750/140km/h	6,00	98M	6,0	401445.001
195/50B-10 (18x8,0-10)	Sava	460	187	750/140km/h	6,00	98M	6,0	401445.002
195/50B-10 (18x8,0-10)	Kenda	460	187	750/140km/h	6,00	98M	6,0	401445.003
195/55R10-C*	Trailermaxx	468	201	750/140km/h	6,25	98P	7,0	401445.005
195/55R10-C*	Security	468	201	750/140km/h	6,25	98N	7,0	401445.007
195/55R10-C*	Eternity	468	201	750/140km/h	6,25	98N	7,0	401445.008
Reifengröße 12"	Fabrikat	Aussen- durchmesser mm	Reifen- breite mm	Tragkraft kg	Reifendruck max. in bar	Index	Gewicht kg	Bestell- nummer
140/70R12-C	Mastertrail	506	141	530/140km/h	4,30	86N	4,9	408621.001
145R12-C	Trailermaxx	543	147	530/140km/h	4,50	86N	7,0	405177.001
155R12-C	Nangkang	556	156	560/140km/h	4,50	88Q	7,9	405178.002
155/70R12-C*	Security	525	163	900/140km/h	6,25	104/102N	7,4	400169.002
185/60R12-C*	Security	527	185	900/140km/h	6,50	104/101N	7,3	411566.002
195/60R12-C*	Security	530	195	900/140km/h	6,50	108/106N	7,9	414872.001
225/55R12-C*	Maxxis	554	228	900/140km/h	5,30	104N	9,2	403845.001
225/55R12-C	Kenda	554	228	1120/140km/h	5,30	112N	9,2	403845.002

Hinweis: Nach 20km und höchstens 100km müssen die Radmuttern nachgezogen werden!

* = mit M+S Kennung

Andere Ausführungen auf Anfrage. Änderungen vorbehalten.